



NOVA II
2x1



NOVA II
1x1



NOVA 9°
2x1

Light Engine	BLAIR-CG	BLAIR-CG	BLAIR
Product Family	NOVA II	NOVA II	NOVA 9°
Color Adjustment	Tunable Color	Tunable Color	Tunable White
Indigo Emitter	✓	✓	✓
Extended Red Emitter	✓	✓	✓
Color Space Coverage	90% Rec.2020	90% Rec.2020	70% Rec.2020
CCT Range	1,800K - 20,000K	1,800K - 20,000K	1,800K - 20,000K
White Light Quality	SSI [P3200] = 90 SSI [D5600] = 86	SSI [P3200] = 90 SSI [D5600] = 86	SSI [P3200] = 89 SSI [D5600] = 86
Native Output (5,600K @ 5M)	10,217 lux	4,788 lux	29,730 lux
Native Beam Angle	35°	35°	9°
Beam Angle Using Included Flat Diffuser	95°	95°	80°
Pixel Count	2	1	4
Max Power Consumption	1250W	650W	800W
AC Power Passthrough	✗	✓	✓
x,y Coordinates	✓	✓	✓
HSIC+	✓	✓	Limited HSIC+
Gel Mode	✓	✓	✗
Control Methods	On-board, Sidus Link, Sidus Link Pro, DMX512, CRMX, Art-Net/sACN, RDM	On-board, Sidus Link, Sidus Link Pro, DMX512, CRMX, Art-Net/sACN, RDM	On-board, Sidus Link, Sidus Link Pro, DMX512, CRMX, Art-Net/sACN, RDM
Data Ports	1x 5-pin DMX in, 1x 5-pin DMX out, 2x locking RJ45	1x 5-pin DMX in, 1x 5-pin DMX out, 2x locking RJ45	1x 5-pin DMX in, 1x 5-pin DMX out, 2x locking RJ45
Modifier Mount	QuickClip	QuickClip	QuickClip
Removable Yoke	✓	✓	✓
Fixture Mount	Junior Pin	Junior/Baby Combo	Junior Pin
IP Rating	IP65	IP65	IP65
Weight - Lamp Head with Yoke	18.65 kg / 41.12 lbs	11.35 kg / 25.02 lbs	19.65 kg / 43.32 lbs
Dimensions - Lamp Head with Yoke	82.9 x 56.6 x 15.4cm 32.7 x 22.3 x 6.1in	49.2 x 57.9 x 15.6 cm 19.4 x 22.8 x 6.1 in	82.9 x 56.6 x 15.4 cm 32.7 x 22.3 x 6.1 in
Designed for Accessories	NOVA 2x1 Softbox NOVA 2x1 Dome Diffuser (Heavy Frost) NOVA 2x1 Dome Diffuser (Light Frost) NOVA 2x1 Fabric Control Grid NOVA 2x1 Rolling Hard Case Dual Quick Release to Truss Clamp Adapter	NOVA 1x1 Softbox NOVA 1x1 Dome Diffuser (Heavy Frost) NOVA 1x1 Dome Diffuser (Light Frost) NOVA 1x1 Fabric Control Grid NOVA 1x1 Rolling Hard Case Dual Quick Release to Truss Clamp Adapter	NOVA 9° 2x1 3-Light Kit NOVA 2x1 3-Light Yoke Kit (Bare Ends) NOVA 2x1 3-Light Yoke Kit (CEE 16A) RCAC3F-X to AC Power Cable (6m) (20A Max) RCAC3F-X to CEE 16A AC Power Cable (6m) (20A Max) NOVA 2x1 Rolling Hard Case NOVA 2x1 Softbox NOVA 2x1 Dome Diffuser (Heavy Frost) NOVA 2x1 Dome Diffuser (Light Frost) NOVA 2x1 Fabric Control Grid Dual Quick Release to Truss Clamp Adapter
Compatible with Accessories	NOVA 2x1 3-Light Yoke Kit (Bare Ends) NOVA 2x1 3-Light Yoke Kit (CEE 16A) RCAC3F-X to AC Power Cable (6m) (20A Max) RCAC3F-X to CEE 16A AC Power Cable (6m) (20A Max) Sidus One Sidus Four	Sidus One Sidus Four RCAC3F-X to AC Power Cable (6m) (20A Max)	Sidus One Sidus Four