



Quick Dome 90

Main Features

- ø90cm Bowens mount circular soft box with **16 steel support rods**
- **Quick-release latch** on speed ring allows users to **bring all rods to tension in seconds**
- **Extended lateral side handle** allows easy handling and manipulation of Quick Dome during mounting and unmounting
- **Snap-in removable Bowens mount chuck** allows for easy part replacements
- **Packs flat and compactly**
- **Diffuse and soften** hard point source lighting fixtures
- Includes 2 front diffusion cloths (**1 and 2 stop**) and inner baffle
- **40° fabric light control grid** included
- **Deep parabolic design** for uniform light output distribution
- **Highly reflective silver inner** lining for optimized light output
- Includes **carrying bag**

Specifications

Dimensions	Built	ø89.0 x 60.0cm ø35.0 x 23.6in
	Collapsed	92.0 x 7.0 x 5.7cm 36.2 x 2.8 x 2.2in
Weight	1.40kg / 3.09lbs	

Photometrics

CCT	Dis.	STORM 700x, 1 Stop Diff., No Grid	STORM 700x, 1 Stop Diff., w/ Grid	STORM 700x, 2 Stop Diff., No Grid	STORM 700x, 2 Stop Diff., w/ Grid
2,500K	3m	1,972 lux 183 fc	1,657 lux 154 fc	1,206 lux 112 fc	988 lux 92 fc
	5m	715 lux 66 fc	560 lux 52 fc	432 lux 40 fc	337 lux 31 fc
3,200K	3m	2,329 lux 216 fc	1,955 lux 182 fc	1,422 lux 132 fc	1,161 lux 108 fc
	5m	845 lux 79 fc	661 lux 61 fc	510 lux 47 fc	398 lux 37 fc
4,300K	3m	2,877 lux 267 fc	2,412 lux 224 fc	1,755 lux 163 fc	1,431 lux 133 fc
	5m	1,044 lux 97 fc	819 lux 76 fc	631 lux 59 fc	492 lux 46 fc
5,600K	3m	2,910 lux 270 fc	2,432 lux 226 fc	1,771 lux 165 fc	1,445 lux 134 fc
	5m	1,053 lux 98 fc	826 lux 77 fc	638 lux 59 fc	495 lux 46 fc
6,500K	3m	2,840 lux 264 fc	2,377 lux 221 fc	1,729 lux 161 fc	1,408 lux 131 fc
	5m	1,030 lux 96 fc	808 lux 75 fc	619 lux 58 fc	484 lux 45 fc
7,500K	3m	2,622 lux 244 fc	2,193 lux 204 fc	1,596 lux 148 fc	1,298 lux 121 fc
	5m	950 lux 88 fc	744 lux 69 fc	570 lux 53 fc	446 lux 41 fc
10,000K	3m	2,165 lux 201 fc	1,815 lux 169 fc	1,317 lux 122 fc	1,071 lux 100 fc
	5m	783 lux 73 fc	614 lux 57 fc	472 lux 44 fc	369 lux 34 fc



Product Description

The Aputure Quick Dome 90 is a 90cm circular Bowens mount softbox built for fast, reliable, and professional light shaping on set. Its quick-release latch mechanism on the speed ring allows users to tension all 16 steel support rods within seconds, streamlining both setup and teardown. The extended lateral side handle provides improved control and comfort when mounting or unmounting the softbox from the front of Bowens mount fixtures, while the snap-in removable Bowens mount chuck enables easy part replacements when necessary.

With a deep parabolic design and highly reflective silver interior, the Quick Dome 90 produces a uniform and powerful soft light output that maintains smooth luminance from center to edge. It includes two front diffusion cloths (1 and 2 stop), an internal baffle, and a 40° fabric light control grid, allowing users to adjust diffusion strength and directionality for precise lighting control.

Designed with portability in mind, the Quick Dome 90 packs flat and compactly into its included carrying bag, making it simple to transport and store. With its durable steel support rods and universal Bowens mount, the Quick Dome 90 pairs seamlessly with STORM, Electro Storm, and Light Storm fixtures, offering filmmakers and photographers a dependable and efficient soft light solution for professional productions.

Sales & Shipping Information

Product Name	Quick Dome 90
SKU	AA07060382
UPC	6977162455785
Packing Dimensions	91.0 x 26.5 x 12.0cm / 35.8 x 10.4 x 4.7in
Net Weight	1.40kg / 3.09lbs
Gross Weight	2.27kg / 5.00lbs
Carton Quantity	3 pcs
Carton Dimensions	92.7 x 38.3 x 29.5cm / 36.5 x 15.2 x 11.6in
Carton Weight	9.58kg / 21.1lbs

What's in the Box

Name	Qty
Quick Dome 90	1
1 Stop Front Diffusion Cloth	1
2 Stop Front Diffusion Cloth	1
40° Fabric Light Control Grid	1
Inner Baffle	1
Carrying Bag	1



Quick Dome 60

Main Features

- **ø60cm** Bowens mount circular soft box with **16 steel support rods**
- **Quick-release latch** on speed ring allows users to **bring all rods to tension in seconds**
- **Extended lateral side handle** allows easy handling and manipulation of Quick Dome during mounting and unmounting
- **Snap-in removable Bowens mount chuck** allows for easy part replacements
- **Packs flat and compactly**
- **Diffuse and soften** hard point source lighting fixtures
- Includes **1 stop** front diffusion cloth and inner baffle
- **40° fabric light control grid** included
- **Deep parabolic design** for uniform light output distribution
- **Highly reflective silver inner** lining for optimized light output
- Includes **carrying bag**

Specifications

Dimensions	Built	ø58.0 x 32.7cm ø22.8 x 12.8in
	Collapsed	53.0 x 7.0 x 5.7cm 20.9 x 2.8 x 2.2in
Weight	0.76kg / 1.68lbs	

Photometrics

CCT	Dis.	STORM 400x, No Grid	STORM 400x, With Grid
2,500K	3m	1,273 lux 118 fc	1,054 lux 98 fc
	5m	464 lux 43 fc	379 lux 35 fc
3,200K	3m	1,588 lux 148 fc	1,318 lux 122 fc
	5m	572 lux 53 fc	472 lux 44 fc
4,300K	3m	1,682 lux 156 fc	1,390 lux 129 fc
	5m	607 lux 56 fc	501 lux 47 fc
5,600K	3m	1,652 lux 154 fc	1,363 lux 127 fc
	5m	597 lux 55 fc	491 lux 46 fc
6,500K	3m	1,615 lux 150 fc	1,331 lux 124 fc
	5m	583 lux 54 fc	481 lux 45 fc
7,500K	3m	1,577 lux 147 fc	1,302 lux 121 fc
	5m	570 lux 53 fc	472 lux 44 fc
10,000K	3m	1,505 lux 140 fc	1,243 lux 116 fc
	5m	544 lux 51 fc	451 lux 42 fc



Product Description

The Aputure Quick Dome 60 is a 60cm circular Bowens mount softbox designed for fast, reliable, and professional light shaping on compact sets. Its quick-release latch mechanism on the speed ring allows users to tension all 16 steel support rods within seconds, streamlining setup and teardown when working in fast-paced production environments. The extended lateral side handle provides improved grip and control when mounting or removing the softbox from the front of Bowens mount fixtures, while the snap-in removable Bowens mount chuck enables quick and convenient part replacements as needed.

With a deep parabolic design and highly reflective silver interior, the Quick Dome 60 delivers uniform and efficient soft light output that helps maintain smooth luminance from center to edge. It includes a 1-stop front diffusion cloth and an internal baffle for achieving balanced softness, along with a 40° fabric light control grid for shaping spill and directing light with precision.

Engineered for portability, the Quick Dome 60 packs flat and compactly into its included carrying bag for easy transport and storage. Compatible with STORM and Light Storm Bowens-mount fixtures, the Quick Dome 60 offers filmmakers, content creators, and photographers a lightweight yet durable soft light solution optimized for smaller studio setups and on-the-go productions.

What's in the Box

Name	Qty
Quick Dome 60	1
1 Stop Diffusion Cloth	1
Inner Baffle	1
40° Fabric Light Control Grid	1
Carrying Bag	1

Sales & Shipping Information

Product Name	Quick Dome 60
SKU	AA07060383
UPC	6977162455792
Packing Dimensions	55.8 x 26.5 x 12.0cm 22.0 x 10.4 x 4.7cm
Net Weight	0.76kg / 1.68lbs
Gross Weight	1.14kg / 2.51lbs
Carton Quantity	3 pcs
Carton Dimensions	57.5 x 38.3 x 29.5cm 22.6 x 15.1 x 11.6in
Carton Weight	5.89kg / 13.0lbs



Quick Dome 40 Feature Sheet

Main Features

- ø40cm Mini ProLock mount circular soft box with **8 support rods**
- **Rounded octagonal design** for circular reflections
- **Quick-release latch** on speed ring allows users to **bring all rods to tension in seconds**
- **Packs flat and compactly**
- Includes **1 stop and 2 stop** front diffusion cloths and **40° fabric light control grid**
- **Highly reflective silver inner** lining for optimized light output
- **Deep parabolic design** for uniform light distribution
- Includes **carrying bag**

What's in the Box

Name	Qty
Quick Dome 40	1
2-Stop Diffusion Cloth	1
1-Stop Diffusion Cloth	1
Light Control Grid	1
Carrying Bag	1

Photometrics

CCT	Dis.	STORM 80c, 1-Stop Diffusion Cloth	STORM 80c, 2-Stop Diffusion Cloth
1,800K	1m	1,640 lux 152 fc	1190 lux 111 fc
	3m	164 lux 15 fc	113 lux 11 fc
3,200K	1m	2,302 lux 214 fc	1,666 lux 155 fc
	3m	230 lux 21 fc	158 lux 15 fc
4,300K	1m	2,413 lux 224 fc	1,733 lux 161 fc
	3m	238 lux 22 fc	164 lux 15 fc
5,600K	1m	2,398 lux 223 fc	1,734 lux 161 fc
	3m	241 lux 22 fc	166 lux 15 fc
6,500K	1m	2,345 lux 218 fc	1,714 lux 159 fc
	3m	236 lux 22 fc	160 lux 15 fc
10,000K	1m	2,208 lux 205 fc	1,603 lux 149 fc
	3m	220 lux 20 fc	151 lux 14 fc
20,000K	1m	2,003 lux 186 fc	1,447 lux 134 fc
	3m	199 lux 18 fc	137 lux 13 fc



Product Description

The Aputure Quick Dome 40 is a 40cm circular Mini ProLock softbox designed for the STORM 80c, bringing fast, professional soft light control to the smallest production spaces. Its quick-release latch mechanism allows users to tension all 8 support rods in seconds, making setup intuitive for handheld, mounted, and tight-angle lighting applications where space is extremely limited.

With a deep parabolic profile and a highly reflective silver interior, the Quick Dome 40 produces a soft and focused light output that maintains smooth luminance from center to edge, even when positioned just inches away from a subject. It includes both 1-stop and 2-stop front diffusion cloths, as well as a 40° fabric light control grid, allowing creators to tailor softness and spill to suit tabletop composition, tight interview framing, or detail-oriented product work.

Compact, lightweight, and optimized for rapid deployment, the Quick Dome 40 packs flat into its included carrying bag for effortless transport. As the smallest member of the Quick Dome family, it delivers efficient soft light shaping for filmmakers and content creators who rely on the STORM 80c to illuminate close-quarters environments and mobile shooting scenarios.

Specifications

Dimensions	Built	Φ44.0 x 23.0cm 17.3 x 9.1in
	Collapsed	37.0 x 9.6 x 3.9cm 14.6 x 3.8 x 1.5in
Weight	0.26kg / 0.57lbs	

Sales & Shipping Information

Product Name	Quick Dome 40
SKU	AA07060384
UPC	6977162455808
Packing Dimensions	37.0 x 9.6 x 3.9cm 14.6 x 3.8 x 1.5in
Net Weight	0.26kg / 0.57lbs
Gross Weight	0.56kg / 1.2lbs
Carton Quantity	8 pcs
Carton Dimensions	47.0 x 46.3 x 37.0cm 18.5 x 18.2 x 14.6in
Carton Weight	7.80kg / 19.19lbs